

UHF Dual Junction Circulator 383MHz-518MHz



Note: Photo is for illustration purposes only.
Please refer to outline drawing.

Product Description

RFLC-117-1-450M is a dual junction circulator with a frequency range of 383 to 518MHz.

The circulator has a minimum isolation of 18dB. The maximum insertion loss is 1.4dB.

The circulator input and output connectors are SMA.

Features

- High power handling up to 200W
- Wide band operation
- High isolation within operational band
- Low Insertion Loss

Typical Applications

- Wireless Infrastructure
- Military and Aerospace Applications
- Test Instrumentation
- Radar Systems
- 5G Wireless Communications
- Microwave Radio Systems
- TR Modules
- Research and Development
- Cellular Base Stations

Electrical Specifications (T_A=+25°C)


Parameter	Min.	Typ.	Max.	Units
Frequency Range		383 - 518		MHz
Insertion Loss	1-2		0.4	dB
	2-3		1.4	
Isolation	2-1	18		dB
	3-2	36		
VSWR			1.35	:1
Forward Power			200	W
Reverse Power			20	W
Rotation		Clockwise (Standard) Count Clockwise (upon request)		
Input / Output Connectors		SMA-50K		
Weight		-		lbs.
Impedance		50		Ω

Environmental Specifications and Test Standards

Parameter	Description
Operational Temperature	0°C to +70°C (Case Temperature)
Storage Temperature	-50°C to +105°C
Thermal Shock	0°C → +70°C (5 Cycles / 10 hours)
*Random Vibration	MIL-STD-202G Table 214-I, Test Condition Letter C 1.5 Hours Per Axis
Shock	1. Weight >20g, 50g half sine wave for 11ms, Speed variation 3.44m/s 2. Weight <=20g, 100g Half sine wave for 6ms, Speed variation 3.75m/s 3. Total 18 times (6 directions, 3 repetitions per direction).
Altitude	Standard: 30,000 Ft (Epoxy Sealed Controlled Environment) Optional: Hermetically Sealed (60,000 ft. 1.0 PSI min)
Hermetically Sealed (Optional)	MIL-STD-883 (For Hermetically Sealed Units)

*For vibration testing details please see additional information section.


Typical Performance Plots



Mkr	Trace	X-Axis	Value	Notes
1 ▾	S11	450.0000 MHz	-20.21 dB	
2 ▾	S12	450.0000 MHz	-33.50 dB	
3 ▾	S21	450.0000 MHz	-0.22 dB	
4 ▾	S22	450.0000 MHz	-20.63 dB	
5 ▾	S23	450.0000 MHz	-0.36 dB	
6 ▾	S32	450.0000 MHz	-40.34 dB	
7 ▾	S33	450.0000 MHz	-20.30 dB	

SN:20230803

Outline Drawing



Notes:

1. Package Material: Aluminum Alloy / Copper
2. Finish: Nickel Plated
3. All dimensions are in millimeters [inches].

Additional Information

Documentation	Webpage
ESD Policy	https://rflambda.com/pdf/rflambda_esd_control.pdf
Connector Torque Specifications	https://www.rflambda.com/pdf/Torque_Specifications.pdf
Random Vibration Test Standard	https://www.rflambda.com/pdf/rflambda_random_vibration_MIL-STD-202G.pdf

Ordering Information

Part Number	Modification	Description
RFLC-117-1-450M	Connectors SMA-50k	383MHz-518MHz Dual Junction Circulator

Important Notice

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information. RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.